

# CIKOpave Seal

## High solids acrylic floor and wall sealer and curing compound

### Description

CIKOpave Seal is an acrylic resin. It will insure a floor and wall sealing in internal and external application over decorative plasters, masonry surfaces, stamped concrete and concrete floors. CIKOpave Seal is also a curing and sealer compounds for freshly placed concrete to retain adequate moistures and insure full hydration of the cement.

CIKOpave Seal will also insure an excellent bonding to a variety of plasters and coatings.

### Properties

- Easy to apply
- Wide range of colours
- Dust proof.
- Excellent adhesion to all types of plasters and coatings
- Tough finish that seals concrete and natural stone surfaces
- Improves concrete and mortar curing by protecting the cement hydration.
- UV resistance

### Application area

CIKOpave Seal is typically used as a sealing agent in the stamping concrete application.

CIKOpave Seal can be used in:

- Driveways
- "look enhancer" of natural stone and decorative plasters and coatings.
- Parking areas
- Side walks
- Warehouses
- Garden landscaping
- Areas where decorative finishes is required

### Physical Properties

Form	Liquid
Colours	Usually transparent but Wide range of colours is available
Tack free time:	40 - 50 min
Application of second coat	After 12 hours
Foot traffic:	4 hr
Bond strength	> 2 MPa (concrete failure)

### Application instructions

The concrete surface should be free from dust and loose particles. All contamination should be treated well before application of CIKOpave Seal.

Apply using brush, roller or spray machine.

Apply 2 coats of Monoseal onto concrete floors at a rate between 8 - 10 m<sup>2</sup> /ltr.

Note: For coloured sealer avoid applying under direct sunlight.

### Coverage / Rate

CIKOpave Seal should be applied at the rate of 8.0-10.0 m<sup>2</sup>/ltr.

Note : The coverage depends on the floor condition and finish. Consult our technical service department for assistance.

### Packaging

CIKOpave Seal is available in 10 and 20 ltr pails. Larger package are available upon request

## Shelf Life

CIKOpave Seal has a shelf life of 12 months if stored in accordance with CIKO instructions.

## Storage

CIKOpave Seal should be stored under cool enclosed shaded area and temperatures between 5 °C and 35 °C.

## Health & safety

CIKOpave Seal should not come in contact with eyes or to be swallowed. Ensure adequate ventilation and avoid inhalation of vapours.

Applicator should wear suitable cloths, gloves and goggles. Use barrier creams recommended providing additional skin protection. If comes in contact with eyes flush with plenty of fresh water and seek medical advice.

Refer Material Safety Data Sheet for further details.

### **Technical Support**

*For any technical support, do not hesitate to contact CIKO team at any time as CIKO offers on and off site services to end users, specifier and contractors.*

### **More from CIKO Middle East**

A wide range of construction chemical products are manufactured by CIKO Middle East which includes:

- Concrete admixtures and additives
- Waterproofing and damp proof coatings
- Surface treatments
- Flooring and toppings
- Grouts and anchors
- Tile adhesives and grout
- Concrete repair materials
- Adhesives and bonding agent
- Protective coating
- Joint Sealants and Moulding compounds
- Ancillaries

TDS/FT18 Rev.:1 Issue:C

Note: The information presented herein based on the best of our knowledge and expertise for which every effort is made to ensure its reliability. Although all the products are subjected to rigid quality tests and are guaranteed against defective materials and manufacture, no specific guarantee can be extended because results depend not only on quality but also on other factors beyond our control



P.O.Box: 295, Doha, Qatar  
T: (+974) 411 4787 / 411 4790 / 411 4794  
F: (+974) 411 4792  
E-mail: enqurles@clkome.com  
فاكس: +٩٧٤ ٤١١٤٧٩٢